

CARD & QR CODE READER

MULTI-TECHNOLOGY RFID, NFC, BLUETOOTH[®] AND MATRIX CODES




Available in keypad or touchscreen versions



BENEFITS

- Integrated QR code & contactless solution
- Quick reading of QR Codes printed or on your smartphone
- Backward compatible and interoperable



13.56 MHz



BLUETOOTH[®]



QR Code



TTL RS485



Water resistant
EQ IP65



Vandal-proof
IK08



- Add your Logo
- 2 configurable multicolor LEDs

The Architect[®] Blue RFID, NFC, and Bluetooth[®] multi-technology reader is equipped with a QR Code module to enable the identification of employees and visitors.

Identification by QR Code simplifies the management of temporary access in offices, parking lots or any other infrastructure.

SIMPLE AND EASY TO USE

The access control reader by QR Code Architect[®] Blue streamlines visitor access with ease and ultimate dual speed reading.

It guarantees QR Code-reading day and night and in all weather conditions: very bright environments, reflections, indoor or outdoor...

The ergonomic design of the reader enables feedback to the user: double visual led indicator, audible indicator, etc.

MULTI-TECHNOLOGY READER

The reader facilitates the identification of users with different profiles (visitors, employees, tenants, drivers...) by its compatibility with multiple identification technologies.

QR Code

Multi-formats supported (1D & 2D codes): QR Code, Micro QR Code, Code 128, Aztec, and Data Matrix. The QR Code can be printed or simply displayed on your smartphone (e-mails, virtual cards, etc.).

Bluetooth[®] & NFC

The smartphone becomes your access key and removes all the limitations of traditional access control cards. STid offers 6 modes of Prox, long distance or hands-free identification to make your access control both secure and instinctive!

RFID MIFARE[®] DESFire[®] EV2 & EV3

The reader supports the latest MIFARE[®] DESFire[®] EV2 & EV3 contactless technologies with new data security features: Secure Messaging EV2 and Proximity Check.

It supports the use of public security algorithms recognized by specialized and independent organizations in information security (ANSSI and FIPS).

OPEN TECHNOLOGIES FOR EASY INTEGRATION

The reader is compatible with all access control systems and accepts multiple interfaces and protocols (Wiegand, Clock & Data, SSCP[®] and OSDP[™]).

The QR Code module can be installed on all existing compatible Architect[®] Blue readers.

A CUSTOMIZED SCALABLE CONFIGURATION

The Architect[®] Blue reader can be customized to meet your needs: all the features and security levels of the readers in your organization can be upgraded.

The modularity allows to implement new functions such as a keypad or a touch screen.

STANDING THE TEST OF TIME

The design of the reader makes it very robust in harsh environments. It can therefore be used outdoors and offers high levels of resistance to vandalism (certified IK08).

SPECIFICATIONS

Operating frequency/Standards	13.56 MHz: ISO14443 types A & B, ISO18092 Bluetooth®
Technology compatibilities	MIFARE® Ultralight® & Ultralight® C, Classic & Classic EV1, Plus® (S/X) & Plus® EV1, DESFire® 256, EV1, EV2 & EV3, PicoPass® (CSN only), iCLASS™ (CSN only) STid Mobile ID® (NFC HCE and Bluetooth® virtual card), Orange Pack ID
Functions	Read only CSN and secure (file, sector) / Protocol driven (read write)
Communication interfaces & protocols	TTL Clock&Data (ISO2) or Wiegand output (encrypted option - S31) / RS485 output (encrypted option - S33) with secure SSCP® v1 and v2 communication protocols, OSDPT™ v1 (plain communication) and v2 (SCP secure communication) Compatible with EasySecure interface
Matrix code reader	1D & 2D codes: QR Code versions 1, 2 and 3; Micro QR Code; code 128; Aztec and Data Matrix Different formats: hexadecimal; decimal; ASCII; raw (in OSDPT™) Detection under ambient lighting from 0 to 100,000 LUX / 3 available modes: ECO; normal day and night; intense brightness Adjustable light beam / target brightness and detection sensitivity
Reading distances**	3 cm / 1.18" minimum with a QR Code (depending on the size of the code) Up to 8 cm / 3.15" with a MIFARE® DESFire® EV2 card Up to 20 m / 65.6 ft with a Bluetooth® smartphone (adjustable distances on each reader)
Data protection	Yes - EAL5+ secure data storage with certified crypto processor
Light indicator	2 RGB LEDs - 360 colors ▲ ▲ ▲ Configuration by card (standard or virtual), software or external command (0V) depending on interface
Audio indicator	Internal buzzer with adjustable intensity Configuration by card (standard or virtual), software or external command (0V) depending on interface
Relay	Automatic tamper direction management or SSCP® / OSDPT™ command according to the interface
Power requirement	260 mA / 12 VDC max
Power supply	7 VDC to 28 VDC
Connections	10-pin plug-in connector (5 mm / 0.2") / 2-pin plug-in connector (5 mm / 0.2"): O/C contact - Tamper detection signal
Material	ABS-PC UL-V0 (black) / ASA-PC-UL-V0 UV (white)
Dimensions (h x w x d)	156.5 x 80 x 36 mm / 6.3" x 3.15" x 1.02" (general tolerance following ISO NFT 58-000 standard)
Operating temperatures	- 30°C to + 60°C / - 22°F to + 140°F
Tamper switch	Accelerometer-based tamper detection system with key deletion option (patented solution) and/or message to the controller
Protection / Resistance	IP65 Level - Weather-resistant with waterproof electronics (CEI NF EN 61086 homologation) / Humidity: 5 - 90% / Reinforced IK08 certified vandal-proof structure
Mounting	Compatible with any surfaces and metal walls - Wall mount/Flush mount: - European 60 & 62 mm / 2.36" & 2.44" - American (metal/plastic) - 83.3 mm / 3.27" - Dimensions: 101.6 x 53.8 x 57.15 mm / 3.98" x 2.09" x 2.24" - Examples: Hubbel-Raco 674, Carlon B120A-UP
Certifications	CE (Europe), FCC (USA), IC (Canada), UKCA (United Kingdom) and UL
Part numbers y: case color (l: black - 2 white)	Read only secure - TTL ARCS-R31-AQ/BT1-xx/y Read only secure / Secure Plus - TTL ARCS-S31-AQ/BT1-xx/y Read only secure - RS485 ARCS-R33-AQ/BT1-7AB/y Read only secure / EasySecure interface - RS485 ARCS-R33-AQ/BT1-7AA/y Read only secure / Secure Plus - RS485 ARCS-S33-AQ/BT1-7AB/y Read only secure / Secure Plus / EasySecure interface - RS485 ARCS-S33-AQ/BT1-7AA/y Controlled by SSCP® v1 - RS485 ARCS-W33-AQ/BT1-7AA/y Controlled by SSCP® v2 - RS485 ARCS-W33-AQ/BT1-7AD/y Controlled by OSDPT™ v1 & v2 - RS485 ARCS-W33-AQ/BT1-7OS/y

DISCOVER OUR CREDENTIALS AND ERGONOMIC MANAGEMENT TOOLS



13.56 MHz or dual frequency
ISO cards & key holders



QR Codes, Bluetooth® & NFC smartphones
using STid Mobile ID® application



SECard configuration kit and
SSCP® v1 & v2 and OSDPT™ v1 & v2 protocols



Web platform for remote management
of your virtual cards

*Our readers only read the iCLASS™ chip serial number / UID PIC01444-3B. They do not read iCLASS™ cryptographic protection or the HID Global serial number / UID PIC01444-3B.

**Caution: information about the distance of communication: measured from the center of the antenna, depending on the type of credential, size of the credential, operating environment of the reader, temperatures, power supply voltage and reading functions (secure reading). External interference may reduce reading distances.

Legal: STid, STid Mobile ID®, SSCP® and Architect® are registered trademarks of STid SAS. All trademarks mentioned in this document belong to their respective owners. All rights reserved - This document is the property of STid. STid reserves the right to make changes to this document and to cease marketing its products and services at any time and without notice. Photos are not contractually binding.

Headquarters / EMEA

13850 Grésasse, France
Tel.: +33 (0)4 42 12 60 60

PARIS-IDF

92290 Châtenay-Malabry, France
Tel.: +33 (0)1 43 50 11 43

STid UK Ltd.

Gallows Hill, Warwick CV34 6UW, UK
Tel.: +44 (0) 192 621 7884

NORTH AMERICA

Irving, Texas 75063-2670, USA
Tel.: +1 877 894 9135

LATINO AMERICA

Cuahtémoc, 06600 CDMX, México
Tel.: +52 (55) 5256 4706

MIDDLE EAST

Dubai Digital Park, DSO, UAE
Tel.: +971 521 863 656

info@stid.com
www.stid-security.com



AUTHORIZED DISTRIBUTOR

ScreenCheck, a Centena group company, is a leading value added distributor of physical security and identification solutions across the Middle East and Africa. Screencheck provides individual as well as end-to-end integrated solutions for

- ▶ ID Card Issuance
- ▶ Attendance Management
- ▶ Access Control
- ▶ CCTV Solutions
- ▶ A.I Enhanced Security Systems
- ▶ RFID Solutions
- ▶ Speed Gates & Turnstiles
- ▶ Visitor & Workspace Management
- ▶ Data Center Solutions
- ▶ UPS Solutions

and other innovations that meet 21st-century security requirements. The unique solutions are catered to Government, Corporate, Educational, Manufacturing, Retail and other major industries. The global domain expertise and a network of 30+ worlds leading brands under one roof, has made ScreenCheck the entrusted identification and security solutions partner in the region.

SCREENCHECK MIDDLE EAST FZ LLC

#1712, Grosvenor Business Tower, Tecom Area, Dubai, United Arab Emirates.

www.screencheckme.com

Talk to Us:
 **+971 4 3910707**

Write to us:
 **enquiry.screencheckme@centena.com**